



Tilt & Table: motorized height adjustable and tilting mobile stand

for Interactive Flatpanel displays up to 75"

Product datasheet



Tilt & Table mobile double-column motorized height adjustable floor stand

The double-column design guarantees the stability needed to work with Interactive Touchscreens up to 75" diagonal with a 210 Lbs.[95 kg] total weight capacity. The wired remote control unit (no batteries) can be placed at a convenient and easy to reach location, allowing the user to adjust the height and tilt angle of the screen safely and quietly. The motorized stand has an anti collision feature on the height adjust motors to prevent accidental pinching: when the system is moving and senses an obstruction, it will stop and retreat.

The height adjust motor is the fastest in its class at 1.5°per second travel speed [38 mm per second] and has a soft-start and soft-stop. Vesa interfaces for dimensions 400x200, 400x400, 600x200 and 600x400 are integrated in the support frame for the touchpanel. On the topside of the columns there is an enclosed box where the electronic controls are safely located, this lock-box can be used to place a mini-PC, thin-client PC or NUC.

The 26" travel will guarantee full screen access for all users, while the 90 degree tilt feature will allow multiple users to access the screen at the same time (depending on the touchpanel specifications) the product is ideal for wheelchair users.

Please consult our sales manager for questions about optional accessories.

Contact information: Sales manager North America: Sjoerd Ory; phone: +1 778 241 4029; email: s.ory@tregout.com

| 487A03 Tilt & touch mobile motorized height adjustable stand travel 26" black max 210 Lbs. | Part number | Description |
|--|-------------|---|
| | 487A03 | Tilt & touch mobile motorized height adjustable stand travel 26" black max 210 Lbs. |
| | | |
| | | |

V:20171107



Tilt & Table motorized height adjustable and tilting mobile stand for Interactive Flatpanel displays up to 75"

| Technical specifications | Length | Width | Height | Weight | |
|---|---|--------------|-----------------|------------------------|--|
| Product dimensions (without screen) | 28.5" [725] | 30.6"[777] | 28"[710] | 121 lbs [55kg] | |
| Shipping dimensions (boxed) | 44.8"[1140] | 22.5"[570] | 13.8"[350] | 132 lbs [60kg] | |
| Full pallet of 12 EA | 45.2" [1150] | 45.2" [1150] | Appr. 82"[2100] | Appr. 1636 lbs [744kg] | |
| Travel (center of VESA pattern to floor) 26"[660] (horiz. 28" to 54"; vert. 26.2" to 52,2"); Speed 1.5"/Sec. [38 mm/Sec.] | | | | | |
| Tilt feature | Tilt feature 90 degrees from vertical to horizontal | | | | |
| Maximum screen weight (size) | 210 Lbs. [95kg] (75" diagonal) | | | | |
| VESA bracket / screen interface | Included from 200x400, 400x400, 600x200 and 600x400 | | | | |
| Safety / certification Anti-collision feature (on height adjust only); UL registered (UR)*; CE; ISO-EN60950 | | | | UR)*; CE; ISO-EN60950 | |
| Material and color | Steel structural parts, powder coated black RAL9005 | | | | |
| Features Enclosed box; 4" diam. Plastic non-marking wheels; width adjustable control panel mount | | | | | |
| Electric 120V / 60Hz; 200W piezo motor; 10% duty cycle (6min/hour); UL962 cert. | | | | | |







